



Home (/) > Products (/product/) > Android Video Phone (/proc/) > Akuvox VP-R48G Andro



Akuvox VP-R48G Android Video Phone

Tel

Message

Contact Us

Home

(+1) 96 502 2122064

//contact.shtml

//contact.shtml

//

Akuvox

7-inch Touchscreen

- Dual gigabit Ethernet ports
- Premium audio and video quality
- Support 3rd-party apps
- Android 5.1/SIP/RTSP/PoE

Online Inquiry

Description

VP-R48G is a SIP-based, gigabit IP video phone for businesses of various scales featuring a 7" touch screen, a 2M CMOS camera sensor and Android Operating System. This multimedia terminal brings together diverse services for business settings, including high-definition audio and video calling, smooth internet surfing, daily information display and individualized business applications import from one's mobile phone.

The communication efficiency and the business productivity that comes with everything in one screen and a bespoke work mode are immeasurable.

Physical Features

7" capacitive touch screen

Display: TFT LCD, 1024*600 pixels, 16:9 aspect ratio

LED light: 1 power light, 1 network light and 1 message light

28 Keys

RK3066 chipset

Flash memory: 8GB

1GB DDR3 memory

Foot stand

Camera: 2M-pixel CMOS sensor, free rotation

PoE IEEE802.3af

Power adapter: input-AC 100~240V, output-DC 12V/1A

Power consumption: approx.14.4W

Operating temperature: 32~ 104°F(0~ 40°C)

Storage temperature: -4~ 158°F(-20 ~ 70°C)

Operating humidity: 10% ~90% (non-condensing)

Storage humidity: 10% ~ 90% (non-condensing)

Weight: approx. 1.04kg
Akuvox
Dimensions: 240x192x106mm
Open A Smart World
Gift box size: 255x198x128mm

Video Features

Codec: H.263 and H.264

Solution: QCIF, CIF, VGA, 4CIF and 720P

Bitrate: 64kbps-2Mbps

Adaptive bandwidth adjustment

Image format: JPEG, GIF, PNG and BMP

Other feature: PIP, full screen and local video ON/OFF control

Audio Features

Wideband codec: G.722

Narrowband codec: PCMA, PCMU, G.723, G.729, OPUS, ILBC, AMR-NB and AMR-WB

Echo cancellation

Voice activity detection

Comfort noise generator

Full-duplex speakerphone

DTMF mode: RFC2833, In-Band, SIP INFO and Auto

Interface Features

2xRJ45 10/100/1000M Ethernet ports

Bluetooth

Wireless access: 802.11b/g/n

1xUSB flash drive 2.0

1xRJ9 handset

1x3.5mm headset jack

1xHDMI video output port

SIP Features

SIP v2 (RFC3261)

Line: 6 SIP accounts

Android Features

Android Operating System 5.1

Default apps: Phonebook, Weather, Google Play, Digital Photo Frame, Stock, News Feeds, Calendar, World Clock, Alarm Clock, Email, Camera, File Browser, Games

3rd-party Android applications support

Network Features

UDP/TCP/IP
Open A Smart World
RTP/RTCP

ARP/RARP

HTTP/HTTPS

NAT traversal: static NAT configure, SIP Keep Alive

IP assignment: static IP, DHCP or PPPoE

NTP for auto time setting

Network Packet Capture

TFTP/FTP/HTTP/HTTPS client API

QoS: Layer 2 (802.1Q, 802.1p) and Layer 3 (ToS, DiffServ)

MD5 and MD5-sess based authentication

Phone Features

Call Waiting

Call Transfer

Call Hold

Mute

Redial

Speed Dial

DND

Direct IP call

4-way conferencing

Adjustable volume

Selectable ring tones

Directory Features

Local phonebook: up to 3,000 groups

Phonebook with contacts picture

Favorites

Blacklist

Call log: 600 entries (200 missed calls; 200 dialed calls; 200 received calls.)

LDAP

Intelligent search method

Administration Features

Firmware local update: internal SD card or USB flash disk methods


Firmware remote update: FTP method

Auto provisioning: FTP/TFTP/HTTP/HTTPS

System log export support

Akuvox
Return to Factory Default support
Configuration management: touch screen-based management
Open A Smart World
Multi-language support

Online Inquiry

Name	Phone	E-mail *
Content *		
Code		Submit

Previous: No Prev

Next: No Next

Copyright©AKUVOX All rights reserved. Sitemap (/map.shtml) 

